

◆ FEATURES

- 사용자의 선택에 따라 입력형태(10종)을 자유롭게 변경하여 사용이 가능.
- 고성능, 고정도의 16bit A/D CONVERTER 사용.
- Peak Hold 기능을 내장.
- 경보출력 : 2ALARM, 4ALARM
(개별적으로 상,하한 설정 가능)
- OUTPUT: ISOLATION mA, mV, V
- TWO UNIT : 진공 및 압력측정시 mmHg
mmHg=> bar 단위 자동변환.
- RS 485 COMMUNICATION



MODEL HD-6000 -

INPUT type

T/C(K,R,E,J,T type), mA, mV, V
PT 100Ω (DIN), JPT 100Ω (JIS)

OUTPUT

0. NONE
1. 2 ALARM
2. 4 ALARM

POWER

1. AC 110/220 50/60HZ
2. DC 24V (OPTION)

OPTION


1. NONE
2. 4 ~ 20mA or 1 ~ 5V(OUTPUT)
3. RS 485

DIMENSION(외형 및 취부방법)


◆ FRONT VIEW




◆ PANEL CUTTING




◆ SIDE VIEW



◆ 취부 방법



TERMINAL CONNECTION



SPECIFICATIONS(제품사양)

ITEM	SPECIFICATIONS	
INPUT 종류	T/C(K,R,E,J,T TYPE), mA, mV, V PT 100Ω (DIN), JPT 100Ω (JIS)	
SCALING	mA, mV, V	-9999 ~ 9999
	PT 100Ω	-200.0 ~ 800.0
	T/C-K	-200 ~ 1350
	T/C-R	0 ~ 1750
	T/C-E	-200.0 ~ 700.0
	T/C-J	-200.0 ~ 700.0
	T/C-T	-200.0 ~ 400.0
DISPLAY	4DIGIT (RED or GREEN)/0.56inch	
ACCURACY	High value of $\pm 0.2\%$ Full Scale	
INPUT MEASURING CYCLE (BURN OUT OFF)	mA, mV, V	200ms
	T/C, RTD	400ms
INPUT RESISTANCE	VOLT	400kΩ
	mA	250Ω/±0.1 25ppm 저항
	OTHER	1MΩ or More
MAXIMUM SIGNAL RESISTANCE	VOLT	300Ω or Less/Line
	OTHER	1kΩ or Less/Line
RTD MAXIMUM LEAD RESISTANCE	30Ω or Less/Line	
SENSOR POWER	DC 24V/30mA $\pm 0.5\%$ 이내	
CMRR	140dB or More	
NMRR	50dB or More	
PEAK-HOLD FUNCTION	HOLDING SAMPLE RATE 10times/sec DIGITAL DISPLAY : Max. value display	
ALARM 출력	접점출력 상태	Normal open
	Max, switching power	750 VA, 90W
	Max, switching voltage	250V AC, 110V DC
	Max, switching current	5A
	Max, switching capacity	3A DC, AC
POWER SUPPLY	4VA AC 110/220V (50/60Hz) DC 24V $\pm 6V$ (OPTION)	
INSULATION RESISTANCE	FG-INPUT	100MΩ or More(500V AC)
	FG-POWER	100MΩ or More(500V AC)
	POWER-INPUT	100MΩ or More(500V AC)
AMBIENT TEMPER HUMIDITY	OPERATION -10~60℃ / 10~90%	
WEIGHT	APPROX. 500g	
HOUSING MATERIAL	ABS plastic(black)	
DIMENSION	96(W) × 48(H) × 112(D)mm	
INSTALLATION	PANEL MOUNTING TYPE	